

## Type 5 - Heavy Duty Endless Sling (EN)

- Most versatile heavy duty sling
- Readily adjustable to account for wear
- Available from 1-4 plys
- Available up to 12" width
- Capacities up to 107,400 lbs.
- Vertical, choker or basket
- Gorilla-Guard® and Monster Edge® available



## Heavy Duty Endless Sling Specifications

Part #	Width	Ply	Rated Capacity in Pounds					
			Rigging Technique			Basket Leg Angle		
			Vertical	Choker	Basket	60°	45°	30°
EN1-901	1"	1	3,200	2,500	6,400	5,500	4,500	3,200
EN2-901		2	6,400	5,000	12,800	11,100	9,000	6,400
EN3-901		3	9,000	7,200	18,000	15,500	12,700	9,000
EN4-901		4	11,000	8,800	22,000	19,000	15,500	11,000
EN1-902	2"	1	6,400	5,000	12,800	11,100	9,000	6,400
EN2-902		2	12,800	10,200	25,600	22,200	18,100	12,800
EN3-902		3	16,500	13,200	33,000	28,500	23,300	16,500
EN4-902		4	22,000	17,600	43,900	38,000	31,000	22,000
EN1-903	3"	1	9,600	7,600	19,200	16,600	13,600	9,600
EN2-903		2	18,000	14,000	36,000	31,100	25,400	18,000
EN3-903		3	24,700	19,800	49,400	42,800	34,900	24,700
EN4-903		4	32,900	26,300	65,800	57,700	46,600	32,900
EN1-904	4"	1	12,800	10,200	25,600	22,200	18,100	12,800
EN2-904		2	24,000	18,000	48,000	41,500	33,900	24,000
EN3-904		3	34,400	27,500	68,800	59,500	48,600	34,400
EN4-904		4	40,800	32,600	81,500	70,600	57,000	40,800
EN1-905	5"	1	16,000	12,000	32,000	27,700	22,600	16,000
EN2-905		2	28,000	22,400	56,000	48,400	39,500	28,000
EN3-905		3	42,000	33,600	84,000	72,700	59,300	42,000
EN4-905		4	56,000	44,800	112,000	97,000	79,100	56,000
EN1-906	6"	1	19,200	15,300	38,400	33,200	27,100	19,200
EN2-906		2	32,600	26,100	65,300	56,500	46,200	32,600
EN3-906		3	45,900	36,700	91,700	79,400	64,900	45,900
EN4-906		4	61,200	48,900	122,300	105,900	86,500	61,200
EN1-908	8"	1	25,600	20,500	51,200	44,300	36,200	25,600
EN2-908		2	41,000	32,800	81,900	70,900	57,900	41,000
EN1-910	10"	1	32,000	25,600	64,000	55,400	45,200	32,000
EN2-910		2	48,000	38,000	96,000	83,100	67,900	48,000
EN1-912	12"	1	38,400	30,700	76,800	66,500	54,300	38,400
EN2-912		2	53,700	43,000	107,400	93,000	76,000	53,700

\* 1 & 2 ply slings can be tapered upon request.